

SALES SPECIFICATIONS

Sales Specification No : 12470-0A-1

Effective Date : 05/08/2006

Page No. 1 of 1

EASTMAN**PRODUCT NAME****Eastman(TM) EEP****SPECIFICATIONS**

PROPERTY	LIMITS	TEST METHOD
Appearance	Clear and Free of Suspended Matter	ASTM D2090
Acetic Acid, %	0.0200 MAX	ASTM D1613
Water, %	0.0500 MAX	ASTM E1064
Ethyl Alcohol, %	0.10 MAX	TCMD-A-AN-G-GC-418-3-SPEC
Visual Color, pcs	15 MAX	ASTM D1209
Ethyl 3-Ethoxy Propionate, %	99.00 MIN	TCMD-A-AN-G-GC-418-3-SPEC

Notes:

The following properties are guaranteed, but are not determined on all shipments and are not reported on the Certificate of Analysis: Specific Gravity @ 20/20° C: 0.9490-0.9530 BHT, ppm: 50-100 Formaldehyde, ppm: 50 Maximum

Eastman Chemical Company · P.O. BOX 511 · Kingsport, Tennessee 37662 USA · 1-800-EASTMAN · 1-423-229-2000 · www.EASTMAN.comSales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.